DEEP SOAKING TUB

Omnitub 1250×750

1250 × 750 × 625 mm

600 mm internal soaking depth · 625 mm external height

Hand-built Omnigel® · white in stock · any colour made to order · self-levelling feet · 30-year warranty

ORDER OR ASK US ANYTHING

ONLINE	www.omnitub.co.uk
PHONE	+44 1934 751 200
WHATSAPP	+44 1934 751 200
EMAIL	info@omnitub.co.uk

omnitub

1250 × 750 mm

600 mm internal depth · 625 mm external height

DEEP SOAKING TUB

OTD-1250x750-DS

V1.1 · 2026-06-06 · SCALE 1:8 · PLAN · 1 of 3 · A4 LANDSCAPE

VIEWED FROM ABOVE



Specification

DIMENSIONS	1250 × 750 × 625 mm
INTERNAL DEPTH	600 mm
EXTERNAL HEIGHT	625 mm
SOAK DEPTH	up to 600 mm · 525 mm with overflow
OPENING (INTERNAL)	1075 × 600 mm
BASE (INTERNAL)	975 × 500 mm
WATER CAPACITY — EMPTY TUB	~339 L · filled to the 525 mm soak line with no one in
WATER IN USE — BATHER(S) IN THE TUB	~260 L with one bather in
NET WEIGHT	22.8 kg (empty)
FLANGES	A 100 mm · B/C/D 75 mm
VERTICAL FLANGE	35 mm
TAPER	50 mm per side over the depth
CORNER RADIUS	~27.5 mm internal
WASTE	⌀ 52 mm (1½" BSP) hole
MATERIAL	Hand-built Omnigel® · 7-layer built-up system
SURFACE	Hand-polished Omnigel®
COLOUR	Any colour · white shown = BS 4800 00 E 55
INSTALLATION	Above-floor, fully supported & dead level · or undermounted, overmounted, inset, part-submerged or raised
DELIVERY	Free UK Mainland Named Day Delivery · international to 220+ countries
WARRANTY	30-year
MADE IN	Somerset, United Kingdom

DRAWN OE · 2026-06-06

All dimensions in millimetres

ORDERING www.omnitub.co.uk

omnitub

1250 × 750 mm

600 mm internal depth · 625 mm external height

DEEP SOAKING TUB

OTD-1250x750-DS

V1.1 · 2026-06-06 · SCALE 1:8 · PROFILES · 2 of 3 · A4 LANDSCAPE

FOR INSTALLATION

END PROFILE



SIDE PROFILE



35 mm vertical flange · 50 mm taper / side · both profiles

Profiles (no feet): END = section through the width; SIDE = section through the length, drawn to the same scale. Full-width external body with a recessed, tapered soaking well — 50 mm/side over the 600 mm depth, on a 35 mm vertical flange below the flat rim. The "void" is the clearance each side at the base for soil-stack / pipe runs. Flange A 100 mm; B, C, D 75 mm. All dimensions in millimetres.

omnitub

1250 × 750 mm

600 mm internal depth · 625 mm external height

DEEP SOAKING TUB

OTD-1250x750-DS

V1.1 · 2026-06-06 · SCALE 1:8 · INSTALLED · WITH FEET · 3 of 3 · A4 LANDSCAPE

FOR INSTALLATION · WITH FEET

END PROFILE



SIDE PROFILE



Omnitub® self-levelling feet · not fixed height · wind to suit · 700 mm benchmark · adjusts up to ~760 mm · both profiles

Installed on the feet: 4 Omnitub® self-levelling feet (END view shows 2, SIDE view shows 2). They are **not fixed height** — extend, lock, then wind down to suit; commonly set to a **700 mm overall** install height (625 mm tub + 75 mm foot) and adjustable beyond. The underside recess gains 25 mm, giving 100 mm of trap clearance at the waste. No load figure published. All dimensions in millimetres.

GET IN TOUCH

Omnitub Ltd

特 オムニタブ HANDMADE IN SOMERSET

ONLINE	www.omnitub.co.uk
PHONE	+44 1934 751 200
WHATSAPP	+44 1934 751 200
EMAIL	info@omnitub.co.uk
SHOWROOM	Unit 6 Works 22, Bennett Road, Highbridge, TA9 4PW
WORKSHOP	Unit 5 Batch Business Park, Lympsham, BS24 0ES

White is always in stock; every colour is made to order. Self-levelling feet supplied. Every Omnitub is hand built in Somerset from our 7-layer Omnigel® built-up system, backed by a 30-year warranty.